

<b>Section 1: Product Information</b>	
Name:	<b>M-6280</b>
Description:	<b>Synthetic rubber</b>
Use:	Hot applied butyl sealant
MSDS number:	YHAI-2
Appearance and odor:	Black solid, rubber odor
Emergency telephone:	1-800-424-9300 CHEMTREC
Product information:	859-879-2853
Effective date:	8/1/2008
Supersedes date:	9/8/2004

<b>Section 2: Hazardous Ingredients</b>		
A hazard evaluation of this product has been performed. The component listed below is identified as hazardous chemicals under the criteria of the OSHA hazard communication standard (29 CFR 1910.1200).		
<b>Common name / Chemical name</b>	<b>CAS number</b>	<b>Approximate %</b>
Talc / Hydrous magnesium silicate	14807-96-6	30 - 50
Carbon Black	1333-86-4	.5 - 3

<b>Section 3: Emergency and First Aid Procedure</b>	
<b>Eye contact:</b>	Flush eyes with water for at least 15 minutes. If irritation develops, consult a physician.
<b>Skin contact:</b>	Remove contaminated clothing and shoes. Wash affected area with soap and water. If irritation develops, consult a physician. Wash contaminated clothing separately before reuse.
<b>Inhalation:</b>	Medical attention is not normally required.
<b>Ingestion:</b>	Seek medical attention. Unless advised otherwise, induce vomiting by giving either syrup of ipecac followed by 2 glasses of water or by sticking finger down throat.
<i>Note to physician:</i>	Treatment should be directed at preventing absorption, administering to the symptoms as they occur, and providing supportive therapy.

<b>Section 4: Health Effects Summary</b>			
<b>Primary route(s) of exposure:</b>	<b>Eye - yes</b>	<b>Skin - yes</b>	<b>Inhalation - no</b>
<b>Eye contact:</b>	Other than mechanical irritation, no adverse effects are expected.		
<b>Skin contact:</b>	Slight incidental contact is not expected to produce adverse effects.		
<b>Inhalation:</b>	Products of decomposition can irritate the nose, throat, and upper respiratory tract and cause nausea and vomiting.		

**Ingestion:**

Adverse effects are not expected.

**Additional effects (target organs):**

Eye.

**Aggravation of existing conditions:**

Exposure to this product is not expected to contribute to, worsen, or aggravate any existing medical conditions.

**Section 5: Toxicologic Information****Talc****Toxic effects:**

Prolonged and repeated exposure to talc can lead to the development of respiratory disorders (i.e. pneumoconiosis).

**Carcinogenicity - listed by:**

ACGIH: no IARC: no NTP annual report: no OSHA: no

*Note: Due to the composition of this product, the toxic affects from Talc exposure may not apply.*

**Section 6: Occupational Control Procedures****Eye protection:**

Wear chemical splash goggles or safety glasses with side shields.

An eye wash facility should be readily available.

**Skin protection:**

Skin exposure should be minimized as good industrial practice. The use of protective gloves and clothing is, therefore, recommended.

**Respiratory protection:**

Respiratory protection is not usually required.

Industrial hygiene consultation is recommended because airborne exposure levels vary depending on the nature of the operation being performed.

**Ventilation:**

Local exhaust ventilation is recommended when vapors, mists, or dusts can be released.

**Personal hygiene:**

Wash thoroughly after handling, especially before eating, drinking, smoking, or using restroom facilities. Wash contaminated goggles, faceshield, and gloves. Professionally launder contaminated clothing. Discard contaminated shoes.

**Airborne exposure limits****Talc**

ACGIH TLV-TWA: 2 mg/m3 respirable fraction

OSHA PEL: 2 mg/m3 respirable fraction

*Note: Because of this product's physical composition, the release or generation of a dust is not expected to occur under normal conditions of use.*

Section 7:	Fire Protection Information	
<b>Flash point:</b>	450 oF, 232 oC	Test method: Seta-flash closed cup
<b>Explosive limits:</b>	LEL (%) - not applicable	UEL (%) - not applicable
<b>Extinguishing media:</b>	not applicable	
<b>Auto-ignition temperature:</b>		
<i>Small fires:</i>	use dry chemical, halon, water spray, or foam.	
<i>Large fires:</i>	Use water spray, fog, or alcohol foam.	
<b>Special fire fighting procedures:</b>	Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH approved positive pressure self-contained breathing apparatus (SCBA) and full protective clothing.	
<b>Unusual fire and explosion hazards:</b>	May liberate irritating or toxic vapors during combustion or decomposition.	

Section 8:	Reactivity Data	
<b>Stable under normal conditions of storage and use:</b>	yes	
<b>Materials to avoid:</b>		
Acids.		
Oxidizing agents.		
<b>Hazardous polymerization:</b>	Hazardous polymerization will not occur.	
<b>Thermal decomposition products:</b>	If heated to high temperatures, this product may emit the following compounds: Smoke, soot, & toxic fumes (e.g. carbon dioxide & carbon monoxide).	

Section 9:	Spill and Leak Procedures	
<b>Response to spills:</b>	Shovel or scoop spilled product and place in closed containers for further handling and disposal.	
<b>Precautions:</b>	If the airborne concentration exceeds established exposure limits (TLV or PEL), or if high airborne concentrations can occur, evacuate employees and ventilate the area. A supplied air respirator or self-contained breathing apparatus (SCBA), should be used for entry into enclosed spaces, or in areas with inadequate ventilation.	
<b>Disposal methods:</b>	If discarded in its original unused form, this product should be managed (stored/treated/disposed/etc.) at an authorized facility, in compliance with all applicable federal, state, and local requirements. Be sure to contact appropriate government environmental agencies if further disposal guidance is required. Of the methods of disposal currently available, it is recommended that an alternative be selected according to the waste management hierarchy.	

Section 10:	Special Precautions	
<b>Recommended storage practice and conditions:</b>	Store in cool, dry, well ventilated area.	
<b>Container use procedures:</b>	No special precautions are needed. Follow good manufacturing and handling practices.	
<b>Empty container precautions:</b>	This container can be hazardous when empty, because it can retain product residues. Therefore, do not re-use container for food, clothing, or products for human or animal consumption or where skin contact may occur.	

Continued on Next Page

3

**M-6280 Hot Applied Butyl MSDS**

Supplemental section 10 information:

HMIS / NFPA classification - health: 1; flammability: 1; reactivity: 0.

Section 11:	Physical Data
% Non-volatile (by weight):	100
pH:	not applicable
Vapor density (air=1):	not applicable
Solubility in water:	insoluble
Evaporation rate:	not applicable
Vapor pressure (mmHg @25oC):	not established
Specific gravity (water=1):	>1
Approximate boiling point:	not applicable
Supplemental section 11 information:	VOC = 0 g/L
<i>Note: The physical data presented above are typical values and should not be construed as a specification.</i>	

Section 12:	Label and Transportation Information
DOT shipping name:	non-regulated
DOT label:	not applicable
DOT identification No.:	not applicable
Supplemental section 12 information: Non-regulated by 49 CFR, IATA/ICAO, IMO	

Section 13:	Regulatory Information
Toxic substance control act (TSCA)	
Chemical component(s) in this product or (b) chemical substance inventory listing (40 CFR 710).	
SARA title III information	
Section 313 - toxic chemicals	
Pursuant to section 313, this product does not contain a toxic chemical in excess of 1 percent of the mixture (0.1 percent, if the listed toxic chemical is a carcinogen).	
Section 302 - extremely hazardous substances	
Pursuant to section 302, this product does not contain an extremely hazardous substance.	
Section 311/312 - hazard categories	
Pursuant to section 311/312, the physical and health hazard categories for this product are identified below:	
Fire hazard:	no
Sudden release of pressure hazard:	no
Reactivity hazard:	no
Immediate (acute) health hazard:	yes
Delayed (chronic) health hazard:	no
Hazardous materials information review regulation - Canada	
This material safety data sheet provides information that complies with the requirements set forth under the Canadian workplace hazardous materials information system (WHMIS).	
Claim for exemption registry No.:	not applicable
Filing date for claim:	not applicable

**Section 14:****Users Responsibility**

A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information contained herein should be passed on to your customers or employees, as the case may be.

**Disclaimer of liability**

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representations of warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

-----  
If you have questions with regard to health effects, or other information presented in this document, contact:

Neil Dalton

Director of Environment, Health and Safety

Yokohama Tire Corporation

1500 Indiana Avenue

Salem, VA 24153

Tel.) 540-375-8209

Fax.) 540-375-0226

End of MSDS

5

State of California Addendum to the Material Safety Data Sheet

Product name:

**M-6280**

Effective date:

8/1/2008

The California safe drinking water and toxic enforcement act of 1986, otherwise known as proposition 65, requires that persons potentially exposed to certain substances be made aware of the chronic effects of the substances specified by the state of California.

This product contains the following substances known to the state of California to cancer, birth defects, or other reproductive harm.

**Ingredients**

Talc

Carbon Black

End of MSDS

6

**M-6280 Hot Applied Butyl MSDS**

Commonwealth of Pennsylvania Addendum to the Material Safety Data Sheet

Product name: **M-6280**

Effective date: 8/1/2008

All of the materials in this product that are required by the Commonwealth of Pennsylvania to be identified are listed below. In addition, some of the materials identified may have been placed by the Commonwealth of Pennsylvania on their hazardous substance list.

<u>Ingredients</u>	<u>CAS Number</u>	<u>Weight %</u>
Talc	14807-96-6	30 - 50
Non-hazardous trade secret ingredient	Proprietary	40 - 60

*The specific chemical identity of any substance not identified with a chemical abstract service number is being held as a trade secret.*