

MS-90 Glass Primer

Description

MS-90 is a primer for glass bonding. It is primarily used in conjunction with YH America's urethane windshield sealant to provide excellent adhesion to glass substrates and many metal surfaces.

Typical Properties (Not a specification)

Type	1 part, moisture curing
Color	Black
Specific Gravity	0.94
Viscosity (#4 Ford Cup, sec.)	12
Solid Content (%)	25

Application Instructions

Due to the settling nature of the product, each container must be vigorously shaken before each use. Apply a uniform coat of glass primer along the entire periphery of the glass. Brush-equipped manual or robotic dispensing equipment may apply the primer quickly and easily.

Cure Schedules

Allow the primer to dry for 2 minutes minimum, 168 hours maximum. After a delay of 168 hours or more, reprime the surface with a light coat.

Shelf Life

9 months after date of manufacture, when stored at room temperature in original, unopened container.

Rev. 2 7/26/02 (HCM1)



103 Kuhlman Drive, Versailles Kentucky 40383, (859) 879-2855 Fax (859) 879-0574

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and of use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by following these suggestions. Nothing contained herein is to be construed as recommendation for use in violation of any patents or of applicable laws or regulations.

Storage and Handling

Flammable liquid, keep away from heat, sparks, and open flame. Store in a cool, dry, well-ventilated area.

See Safety Precautions for safe handling instructions.

Safety Precautions

MS-90 Glass Primer is for industrial use only.

Always use protective goggles, gloves, respiratory equipment and appropriate work clothing when handling.

Avoid eye and skin contact. Wash thoroughly after handling.

Do not breathe vapors. Use with adequate ventilation.

Refer to the Materials Safety Data Sheets for more information.

Availability

MS-90 Glass Primer is available in one quart cans and five-gallon pails.

The product is shipped from our Versailles, Kentucky plant.

Rev. 2 7/26/02 (HCM1)



103 Kuhlman Drive, Versailles Kentucky 40383, (859) 879-2855 Fax (859) 879-0574

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and of use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by following these suggestions. Nothing contained herein is to be construed as recommendation for use in violation of any patents or of applicable laws or regulations.

